




# FOGTAC

*Strong positioning spray adhesive  
for Infusion & RTM*



## DESCRIPTION

**FOGTAC** spray adhesive, designed to be used for vacuum infusion and RTM process, ensures perfect bonding of reinforcement layers during draping process.

It has a powerful bonding force, halfway between INFUTAC and MEGATAC.

With its mist effect, the evaporation of the solvents is facilitated and allows to obtain a quick tack on the surface of the reinforcements, while limiting the quantity deposited between the different layers.

**FOGTAC** adhesive does not interfere with resin flow, and therefore does not generate marking problems.

## INSTRUCTIONS

Shake well before use. Application temperatures between 15°C and 40°C.

Ensure surface is clean, dry, and free of contamination.

Set the nozzle on L (Low) M (Middle) or H (High) to adjust the flow.

Spray a thin layer of adhesive on the surface to be bonded, at a distance of 15/20 cm.

Allow to dry (10 s) until a slightly viscous appearance is obtained. Apply the fabric to be bonded.

## PROPERTIES

Colour	Spray pattern	Aerosol volume	Expiry date	Packaging	Flammability
Green	Fog	500 ml	18 months	Carboard box of 12 cans	Very flammable

The **FOGTAC** adhesive is compatible with most resins but remains under user validation.



COMPLY WITH CLP2015  
REGULATION  
applicable since 01/06/2015

**TOLUENE  
FREE**

Ind A  
Application date 01/2023